

# 支持管の種類

## KINDS OF SUPPORTING PIPE

### 支持管標準寸法重量一覧表

#### SUS304(ステンレス鋼鋼管)

材質：(JIS G3459)

呼称	外径 mm	内径 mm	肉厚 mm	断面積 mm <sup>2</sup>	断面係数 cm <sup>3</sup>	重量 kg/m	定尺 m	定尺重量 kg
32A	42.7φ	36.7φ	3.0	374	3.47	2.94	4.0	11.76
		34.7	4.0	486	4.31	3.82	4.0	15.28
40A	48.6	42.6	3.0	430	4.62	3.37	4.0	13.48
		40.6	4.0	560	5.78	4.40	4.0	17.60
50A	60.5	54.5	3.0	542	7.42	4.25	4.0	17.00
		52.5	4.0	710	9.41	5.57	4.0	22.28
65A	76.3	70.3	3.0	691	12.2	5.42	4.0	21.68
		68.3	4.0	904	15.6	7.13	4.0	28.52
80A	89.1	83.1	3.0	811	16.9	6.37	4.0	25.48
		81.1	4.0	1069	21.8	8.39	4.0	33.56
90A	101.6	95.6	3.0	929	22.3	7.29	4.0	29.16
		93.6	4.0	1226	28.8	9.63	4.0	38.52
100A	114.3	108.3	3.0	1049	28.4	8.23	4.0	32.92
		106.3	4.0	1386	36.9	10.9	4.0	43.6
125A	139.8	131.8	4.0	1707	56.3	13.4	4.0	53.6
		129.8	5.0	2117	68.9	16.6	4.0	66.4
150A	165.2	157.2	4.0	2026	79.7	15.9	4.0	63.6
		155.2	5.0	2516	97.8	19.8	4.0	79.2
		153.2	6.0	3001	115.0	23.6	4.0	94.4

#### BST(黄銅管)

材質：(JISH 3300)

外径 mm	内径 mm	肉厚 mm	断面積 mm <sup>2</sup>	断面係数 cm <sup>3</sup>	重量 kg/m	定尺 m	定尺重量 kg
38.1φ	32.1φ	3.0	331	2.69	2.84	5.0	14.2
44.5	38.5	3.0	390	3.79	3.40	5.0	17.0
50.8	44.8	3.0	450	5.09	3.87	5.0	19.35
63.5	57.5	3.0	571	8.24	4.90	5.0	24.5
76.2	70.2	3.0	690	12.1	5.93	5.0	29.65
88.9	82.9	3.0	810	16.81	6.96	5.0	34.8
	78.9	5.0	1318	26.2	11.3	5.0	56.5
101.6	95.6	3.0	929	22.25	7.99	5.0	39.95
	91.6	5.0	1517	34.9	13.0	5.0	65.0
110.0	100.0	5.0	1649	41.4	14.2	5.0	71.0
114.3	104.3	5.0	1716	44.93	14.65	5.0	73.25
140.0	130.0	5.0	2121	89.1	18.2	5.0	91.0
160.0	150.0	5.0	2435	91.49	20.9	5.0	104.5